



EQUITY FACADE

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 U_w from 0.6 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **50 mm.**
 Minimum glazing: **4 mm**

SECTIONS INWARDS	Mullion 52 mm. Transom 52 mm.
PROFILE THICKNESS	Mullion 2.1 and 3 mm. Transom 2.1 mm.
MAXIMUM DIMENSIONS	Hidden Top Hung Width max. (L) = 2,500 mm. Height max. (H) = 2,500 mm. Width min. (L) = 500 mm. Height min. (H) = 650 mm. Hidden Parallel Projecting Width max. (L) = 2,000 mm. Height max. (H) = 3,000 mm. Width min. (L) = 530 mm. Height min. (H) = 530 mm.
MAXIMUM WEIGHT	Hidden Top Hung 180 Kg Hidden parallel projecting 200 Kg Fix vents 750 Kg

Please consult maximum dimensions according to types.

EXTRUSION ALLOY	6063 T-5
THERMAL BREAK	Combination of PVC Profiles 6,12 or 30 mm
GASKETS	GASKETS EPDM Optionally Totally Vulcanized Corner Gasket
OPTIONS FOR COVERS	Elliptical: 85 mm depth. H-shaped cover: 34 mm depth. Rectangular: 14, 19, 100 and 145 mm depth. Piramidal-shaped: 155 mm depth.
OPENING POSIBILITIES	Hidden Top Hung Hidden Paralel Projecting Hidden Side Hung or Turn&Tilt (In TP-52)

FINISHES

Colour powder coating
 (RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualidéco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

