



# FACADE TP-52

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient  
 **$U_w$  from 0.6 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## GLAZING

Maximum glazing: **50 mm.**  
 Minimum glazing: **4 mm**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12152:2000):

Water tightness (UNE-EN 12154:2000):

Wind resistance (UNE-EN 13116:2001):

Reference test 3.00 x 3.50 m.

**Class AE**

**Class RE<sub>1500</sub>**

**COMPLIES** (Design windload 2000Pa / Security windload 3000Pa)

<b>PROFILE THICKNESS</b>	Mullion 2.1 and 3 mm. Transom 2.1 mm.	<b>EXTRUSION ALLOY</b>	6063 T-5
<b>WINDOW MAXIMUM DIMENSIONS</b>	Hidden Top Hung Width max. (L) = 2,500 mm. Height max. (H) = 2,500 mm. Width min. (L) = 500 mm. Height min. (H) = 650 mm. Hidden Parallel Projecting Width max. (L) = 2,000 mm. Height max. (H) = 3,000 mm. Width min. (L) = 530 mm. Height min. (H) = 530 mm. Hidden Side Hung or Turn&Tilt Width máx. (L) = 1,400 mm. Height máx. (H) = 1,900 mm. Width min. (L) = 500 mm. Height min. (H) = 6000 mm.	<b>THERMAL BREAK</b>	Combination of PVC Profiles 6, 12 or 30 mm
<b>MAXIMUM WEIGHT</b>	Hidden top hung 180 Kg Hidden parallel projecting 200 Kg Hidden side hung / turn&tilt 100 Kg Fix vents 750 Kg	<b>GASKETS</b>	GASKETS EPDM Optionally Totally Vulcanized Corner Gasket
		<b>OPTIONS FOR COVERS</b>	Elliptical: 85 mm depth. H-shaped cover: 34 mm depth. Rectangular: 14, 19, 100 and 145 mm depth. Pyramidal-shaped: 155 mm depth.
		<b>OPENING POSIBILITIES</b>	Hidden Top Hung Hidden Paralel Projecting Hidden Side Hung or Turn&Tilt

Please consult maximum dimensions according to types.

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat Standard > 60 microns

Wood effect powder coating

According to Qualideco Standard

Anodized

According to Ewwa Euras Standard

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured



Certification CWCT.  
British Standard

